

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G01N 33/49	A1	(11) International Publication Number: WO 98/46994 (43) International Publication Date: 22 October 1998 (22.10.98)
(21) International Application Number: PCT/US98/07733 (22) International Filing Date: 16 April 1998 (16.04.98) (30) Priority Data: 60/044,079 17 April 1997 (17.04.97) US (71) Applicant: ETHICON, INC. [US/US]; Route 22, Somerville, NJ 08876 (US). (72) Inventor: SWANZY, James, A.; 2807 Wildplum Drive, Arlington, TX 76015 (US). (74) Agents: CIAMPORCERO, Audley et al.; Johnson & Johnson, One Johnson & Johnson Plaza, New Brunswick, NJ 08933-7003 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TO). Published <i>With international search report.</i>
(54) Title: CHEMICAL INDICATOR AND ITS USE (57) Abstract This invention provides a chemical indicator, in particular, a composition for use as an indicator in hydrogen peroxide plasma sterilization. Said composition comprises both a dye which can change its color when contacted with hydrogen peroxide vapor or plasma derived from hydrogen peroxide, and a certain organic amine compound. A sheet on which the composition is deposited is also provided by this invention.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

CHEMICAL INDICATOR AND ITS USE

5 DETAILED DESCRIPTION OF INVENTION

Technical Field

10 This invention relates to a composition for use as a chemical indicator, in particular, a composition useful in a hydrogen peroxide plasma sterilization treatment, and to a sheet for said treatment on which sheet said composition is deposited.

15

Background Art

20 Since long ago, various kind of sterilization means have been applied to articles of every species such as disposable or recyclable medical apparatuses and food containers, and there have also been proposed indicators for conveniently distinguishing whether such a sterilization treatment has been made or not. For example, Japanese Patent Application Laid-Open (Kokai) No. 59-36172/1984 discloses an indicator for gas
25 sterilization treatment with use of ethylene oxide; and Japanese Patent Application Laid-Open (Kokai) Nos. 61-287972/1986, Hei 5-43827/1993 and Hei 5-65441/1993 each disclose an indicator ink for electron beam sterilization. The latter group of Laid-Open (Kokai) Applications each
30 mention an indicator wherein a pH indicator is used in combination with such a high molecular compound as is capable of generating hydrogen chloride when irradiated with electron beam.

35

On the other hand, as a means to conduct a sterilization treatment without adversely affecting medical equipments which are produced from various materials, there have recently been

proposed and put into practice a hydrogen peroxide plasma sterilization method and an apparatus therefor (See: Japanese Patent Publication (Kokoku) Nos. Hei 2-62261/1990 and Hei 7-22693/1995). This sterilization method summarily comprises a
5 step of contacting an article to be sterilized with hydrogen peroxide vapor under reduced pressure in an air-tight chamber, and then generating hydrogen peroxide plasma. This method can be said to be a very useful one, not only in that high
sterilization efficiency is attained but also in that hydrogen
10 peroxide is converted into water and oxygen which are quite harmless.

The above-mentioned Japanese Patent Publication (Kokoku) No. Hei 7-22693/1995 discloses a liquid-dispensing cassette to
15 be used in a plasma sterilization apparatus which cassette is equipped with a cell for containing a hydrogen peroxide solution. It is further disclosed that said dispensing cassette may be equipped with an indicator strip having such color tone with which to detect the leakage of hydrogen
20 peroxide solution from the liquid-containing cell. Said Publication does not concretely disclose, however, how to constitute the indicator strip.

25 PROBLEMS WHICH THIS INVENTION INTENDS TO SOLVE

Also in putting a hydrogen peroxide plasma sterilization method into practice, it would be desirable that there is
available such an indicator which can easily distinguish
30 whether or not a sterilization treatment has been given to an article to be sterilized, as is employed in the aforementioned gas sterilization treatment with use of ethylene oxide or electron beam sterilization treatment. Thus, the object of this invention is to provide a chemical indicator composition
35 (indicator ink, in particular) which can distinguish whether

or not a hydrogen peroxide plasma sterilization treatment has been given to an article to be sterilized.

5 MEANS TO SOLVE THE PROBLEMS

The aforementioned Japanese Patent Application Laid-Open (Kokai) No. Hei 5-65441/1993, for example, suggests that, when bisphenols and a substance such as triphenylsulfonium
10 hexafluorophosphate which generates acid or free radical when irradiated with electron beam are compounded with an indicator ink which comprises a pH indicator and such a high molecular compound as generates hydrogen chloride when irradiated with electron beam, there can be improved color changeability of
15 said ink when the ink is irradiated with electron beam. The inventors of the present invention, on the other hand, have found out that, when a dye belonging to a specific pH indicator is brought into contact with a system which comprises hydrogen peroxide and plasma derived from hydrogen
20 peroxide and which does not generate hydrogen chloride, there occurs a certain color change, which can be both stabilized and rendered distinct when a certain organic amine is made to co-exist.

25 Thus, in order to achieve the above-mentioned object, this invention provides a composition for use as a chemical indicator which comprises both a dye which can change its color when contacted with at least one substance selected from the group consisting of hydrogen peroxide and plasma derived
30 from hydrogen peroxide, and an organic amine compound which does not evaporate under ambient conditions.

This invention further provides a sheet used for distinguishing whether a hydrogen peroxide plasma
35 sterilization treatment has been made or not, which sheet has, deposited on its substrate, both a layer containing such a

composition (or indicator ink) and an overcoat layer which is provided on said layer.

5 This invention which has the aforementioned features makes it possible to clearly distinguish whether medical apparatuses, food containers and the like have undergone or not such a hydrogen peroxide plasma sterilization treatment, even after a certain time has passed from said treatment.

10

EMBODIMENTS OF INVENTION

As for the dye, in the composition of this invention for use as a chemical indicator, which can change its color when
15 contacted with at least one substance selected from the group consisting of hydrogen peroxide and plasma derived from hydrogen peroxide, there can be employed dyes of any kind so long as they make it possible, owing to their change in color before and after said contact, to clearly distinguish whether
20 such a contact has been made or not. Typical examples of such dyes, although not restricted, are pH indicators which have a transition interval in a range from pH 5.5 ~9.0. Concrete examples of such pH indicators include 1,2-dihydroxy anthraquinone (pH 5.5 ~6.8); dibromothymol sulfonphthalein
25 (Bromothymol Blue: pH 6.0 ~7.5); 5,8-quinolinequinon-8-hydroxy-5-quinolyl-5-imide (pH 6.0 ~8.0); 3-amino-6-dimethylamino-2-methylphenazine hydrochloride (pH 6.8 ~8.0); phenolsulfonphthalein (Phenol Red: pH 6.8 ~8.4); o-cresolsulfon phthalein (Cresol Red: pH 7.2 ~8.8); m-
30 cresolsulfon phthalein (pH 7.4 ~9.0) and the like, and their derivatives. In practical use, two or more of these indicators may be combined with one another.

This invention is characterized in that the above dye is
35 used along with an organic amine compound which does not evaporate under ambient conditions (concretely, at a room

temperature at which the sterilization treatment is made). Any kind of such organic amine compounds are usable so long as they do not evaporate throughout sterilization treatment, in particular a low temperature sterilization treatment with use
5 of hydrogen peroxide (See: for example, Japanese Patent Publication (Kokoku) No. Hei 2-62261/1990; Thus cited, this Publications constitute a part of the present invention), and so long as they can adjust pH of the composition to alkaline side. Examples of such organic amine compounds include mono
10 higher aliphatic amine such as laurylamine, mono hydroxy higher aliphatic amine and triethanol amine. Among these, triethanol amine is preferably employed in consideration of compatibility with the dye used in this invention and compatibility with synthetic resin which may be included as
15 vehible in the composition.

The composition of this invention can usually contain both a vehicle (including synthetic resin, solvent, and, if necessary, plasticizer as well), which is normally used for
20 the preparation of printing ink, and additive (such as dispersant, stabilizer and thickening agent). As for resin, those derived from any kind of synthetic polymers are usable unless the resins are adversely affected in view of achievement of the object of this invention, when subjected to
25 the aforementioned hydrogen peroxide plasma sterilization treatment, Concrete examples of such synthetic resins include phenolic resin, alkyd resin, urea resin, polyamide resin, acrylic resin and synthetic rubbers.

30 These synthetic resins may be suitably selected in accordance with substrate which is used in processing the composition of this invention into a sheet, and in consideration of how to apply the composition onto the substrate (or of printing method). In the case of indirect
35 application (or offset printing) onto the substrate, for example, there can be employed acrylonitrile-butadiene-styrene

resin which is capable of providing a composition having a considerably high viscosity (about 200 ~2000 P). As such acrylonitrile-butadiene-styrene resin, there can be preferably employed, for example, ABS-800 Extender Base, Clear (Advance Process Supply, Chicago, U.S.A.) on the market. This ABS-800 is preferably employed together with glycerol and monoalkyl glycerol ethers such as 2-butoxyethanol either as a solvent as another vehicle or as an additive, and, under circumstances, also together with ultraviolet light absorber.

10

The above-mentioned composition may comprise 0.3 ~10.0 % by weight of dye, 5 ~15 % by weight of organic amine compound, 45 ~70 % by weight of synthetic resin, 20 ~33 % by weight of solvent (such as monoalkyl glycerol ethers) and 1 ~3 % by weight of glycerol, each on the basis of the total amount of the composition. As for substrate, polystyrene type one is preferably employed although not restrictively, when such an ABS resin as mentioned above is used.

20

From the above-explained composition of this invention, there can be conveniently produced a sheet which has, on its substrate, deposited at least said composition to form an indicator-function layer and an overcoat layer on said indicator-function layer. The overcoat layer may be formed from any components so long as the resulting layer is permeable to hydrogen peroxide vapor or plasma derived from hydrogen peroxide, and so long as said formed layer is transparent or semi-transparent such that the color change of dye can be seen through. Preferably, however, the overcoat layer is formed from a composition which contains those components to form the indicator-function layer, except dye and organic amine compounds but including ultraviolet light absorber instead, and, under circumstances, further including 0.3 ~10 % by weight of wax (e.g., polyethylene wax) on the basis of the total amount of the composition.

35

As for ultraviolet light absorber, those of any species may be employed so long as they are normally used in this field and unless they have adverse effects in view of achievement of the object of this invention. For example, benzotriazole derivatives on the market are preferably used. Typical examples of said derivatives include Tinuvin™ type compounds having sunscreen property produced by Ciba-Geigy, which are to be employed singly or in combination of two or more of them.

The sheet comprising thus formed layers may take a strip-like form, or may be a part of a packaging bag for packing articles to be sterilized.

The indicator-function layer is normally formed on the surface of a breathing sheet which constitutes a part of packaging bag. When packaging bag is so transparent as to show its interior, indicator-function layer may be formed either on the inner side of breathing sheet, or on the inner side of laminate sheet, i.e., inside the packaging bag.

The above-mentioned composition of this invention is homogenized by such a known kneading method as is employed for the preparation of printing ink, and is then deposited on a substrate to form an indicator-function layer and, subsequently, an overcoat layer, in accordance with a known printing method, e.g., offset printing, flexographic printing or gravure printing, and, thus, the sheet of this invention can be produced

EXAMPLES

In the following, this invention is explained in more detail with concrete examples. Percentage in the examples mean "% by weight" unless otherwise specified.

Example 1 Formation of indicator-function layer and overcoat layer:

10

A composition having the following components

	ABS-800 Extender Base	
	(Advance Process Supply)	60 (%)
15	Triethanol amine	10
	Glycerol	2
	Phenol Red (including no acid)	0.5
	2-Butoxyethanol	27.5
	Total	100.0

20

was mixed and kneaded by a roll mill until the composition became homogeneous, and, thus, a composition for indicator was prepared.

25 Apart from the above, a composition having the following components

	ABS-800 Extender Base	
	(Same as above)	60 (%)
30	Dipsal (Sunscreen: made by	
	Scher chemicals Inc.)	2
	2-Butoxyethanol	38
	Total	100

was mixed and kneaded by a roll mill until the composition became homogeneous, and, thus, a composition for overcoat was prepared.

5 Thus prepared composition for indicator and composition for overcoat were printed, in this order, on a white and opaque polystyrene sheet. Thus formed laminate sheet may be cut to a suitable size to be a chemical indicator strip.

10

EFFECTS OF INVENTION

15 This invention provides a composition with which to clearly distinguish whether packed articles such as medical apparatuses have undergone a sterilization treatment or not.

CLAIMS

1. A composition for use as a chemical indicator which comprises both a dye which can change its color when contacted with at least one substance selected from the group consisting of hydrogen peroxide and plasma derived from hydrogen peroxide, and an organic amine compound which does not evaporate under ambient conditions.
2. The composition of claim 1 wherein the dye is a pH indicator which has a transition interval in a range from pH 5.5 ~9.0 and wherein the organic amine compound is triethanol amine.
3. The composition of claim 1 or claim 2 wherein the chemical indicator is used for distinguishing whether a hydrogen peroxide plasma sterilization treatment has been made or not.
4. A sheet used for distinguishing whether a hydrogen peroxide plasma sterilization treatment has been made or not, which sheet has, on its substrate, both an indicator-function layer containing the composition for use as a chemical indicator of claim 1 and an overcoat layer which is provided on said indicator-function layer.
5. The sheet of claim 4 wherein the indicator-function layer further contains both at least one kind of solvent selected from the group consisting of glycerol and monoalkyl glycerol ethers, and a synthetic resin which is compatible with said solvent.

6. The sheet of claim 4 or claim 5 wherein the overcoat layer contains at least one kind of solvent selected from the group consisting of glycerol and monoalkyl glycerol ethers, and a synthetic resin which is compatible with said solvent,
5 and, under circumstances, ultraviolet light absorber and waxes as well.

7. The sheet of any one of claims 4 to 6 wherein the synthetic resin is acrylonitrile-butadiene-styrene resin.
10

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US98/07733

A. CLASSIFICATION OF SUBJECT MATTER IPC(6) :G01N 33/49 US CL :422/38,61 According to International Patent Classification (IPC) or to both national classification and IPC														
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) U.S. : 422/38,61,79,82.05; 436/67,166,169 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched NONE Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) APS														
C. DOCUMENTS CONSIDERED TO BE RELEVANT														
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.												
Y,P	US 5,708,141 A (MOYLE et al) 31 January 1998, see col. 24 lines 11-29	1-7												
Y	US 4,938,860 A (WOGOMAN et al) 03 July 1990, see col. 2 lines 13-23, col.8 lines 44+, col.12 32-43	1-7												
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.														
<table border="0"><tr><td>* Special categories of cited documents:</td><td>*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</td></tr><tr><td>*A* document defining the general state of the art which is not considered to be of particular relevance</td><td>*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</td></tr><tr><td>*B* earlier document published on or after the international filing date</td><td>*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</td></tr><tr><td>*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</td><td>*A* document member of the same patent family</td></tr><tr><td>*O* document referring to an oral disclosure, use, exhibition or other means</td><td></td></tr><tr><td>*P* document published prior to the international filing date but later than the priority date claimed</td><td></td></tr></table>			* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention	*A* document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone	*B* earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art	*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*A* document member of the same patent family	*O* document referring to an oral disclosure, use, exhibition or other means		*P* document published prior to the international filing date but later than the priority date claimed	
* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention													
A document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone													
B earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art													
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*A* document member of the same patent family													
O document referring to an oral disclosure, use, exhibition or other means														
P document published prior to the international filing date but later than the priority date claimed														
Date of the actual completion of the international search 30 JUNE 1998		Date of mailing of the international search report 22 JUL 1998												
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. (703) 305-3230		Authorized officer LYLE ALEXANDER Telephone No. (703) 308-0661												